


VOLVO PENTA

Power Generation Engines

8 LITRE SERIES



13 LITRE SERIES



16 LITRE SERIES



17 LITRE SERIES



Stage II / Tier 2*

Engine	50 Hz/1500 rpm									60 Hz/1800 rpm									GENERATOR EFF. (%)
	CONTINUOUS POWER			PRIME POWER			STANDBY			CONTINUOUS POWER			PRIME POWER			STANDBY			
	kWm	kWe	kVA	kWm	kWe	kVA	kWm	kWe	kVA	kWm	kWe	kVA	kWm	kWe	kVA	kWm	kWe	kVA	
TAD840GE-B	132	122	152	176	162	203	194	178	223	160	147	184	194	178	223	213	196	245	92%
TAD841GE	165	152	190	220	202	253	242	223	278	169	156	194	225	207	259	248	228	285	92%
TAD842GE	196	182	228	261	243	303	287	267	334	196	182	227	261	243	303	287	267	334	93%
TAD843GE	210	195	245	280	260	326	308	286	359	205	191	239	274	254	318	301	280	350	93%
TAD1341GE-B	203	189	236	271	252	315	298	277	346	230	214	267	287	267	334	317	295	369	93%
TAD1342GE-B	227	212	264	303	282	352	333	310	387	259	241	301	345	321	401	377	351	438	93%
TAD1343GE-B	244	227	284	325	302	378	356	331	414	265	246	308	353	328	410	388	361	451	93%
TAD1344GE-B	266	247	308	354	329	411	389	362	452	294	273	341	392	364	455	431	401	501	94%
TAD1345GE-B	291	274	342	388	365	456	431	405	506	294	276	345	392	368	460	431	405	506	94%
TAD1346GE	320	301	377	427	402	502	470	442	552	327	307	384	436	409	512	479	450	563	94%
TAD1641GE-B	323	303	379	430	404	505	473	445	556	364	342	428	485	456	570	546	513	642	94%
TAD1642GE-B	377	355	443	503	473	591	554	521	651	399	375	469	532	500	625	585	550	687	94%
TWD1644GE	416	391	489	555	521	652	610	573	717	437	410	513	582	547	684	640	602	752	94%
TWD1645GE	446	420	525	595	560	700	655	616	770	464	437	545	619	582	727	681	640	800	94%
TWD1744GE	532	500	625	645	606	758	709	666	833	563	529	661	682	641	801	750	705	881	94%

Stage IIIA / Tier 3*

Engine	CONTINUOUS POWER			PRIME POWER			STANDBY			CONTINUOUS POWER			PRIME POWER			STANDBY			GENERATOR EFF. (%)
	kWm	kWe	kVA	kWm	kWe	kVA	kWm	kWe	kVA	kWm	kWe	kVA	kWm	kWe	kVA	kWm	kWe	kVA	
TAD851GE	165	152	190	220	202	253	242	223	278	169	156	194	225	207	259	248	228	285	92%
TAD852GE	186	173	216	248	231	289	273	254	317	185	172	216	247	230	287	272	253	316	93%
TAD853GE	186	175	219	248	233	291	273	257	321	200	188	235	266	250	313	293	275	344	94%
TAD1350GE										184	170	213	245	227	284	269	250	313	93%
TAD1351GE	209	194	243	279	259	324	306	285	356	221	205	256	294	273	341	323	300	375	93%
TAD1352GE	236	219	274	314	292	365	345	321	401	258	240	300	344	320	400	376	350	437	93%
TAD1353GE										293	273	341	391	364	454	430	400	500	93%
TAD1354GE	246	229	286	328	305	381	361	336	420	258	240	300	344	320	400	376	350	437	93%
TAD1355GE	266	251	313	355	334	417	390	367	458	258	242	303	344	323	404	376	353	442	94%
TAD1650GE	295	278	347	393	370	462	433	407	508	329	310	387	439	413	516	483	454	568	94%
TAD1651GE	323	303	379	430	404	505	473	445	556	371	348	435	494	464	580	546	513	641	94%
TWD1652GE	379	360	450	505	480	600	557	529	661										95%
TWD1653GE	410	390	488	547	520	650	604	574	717										95%

Tier 4f*

Engine	CONTINUOUS POWER			PRIME POWER			STANDBY			CONTINUOUS POWER			PRIME POWER			STANDBY			GENERATOR EFF. (%)			
	kWm	kWe	kVA	kWm	kWe	kVA	kWm	kWe	kVA	kWm	kWe	kVA	kWm	kWe	kVA	kWm	kWe	kVA				
TWD1672GE										532	508	635	685	559	698				95.5%			
TWD1673GE													595	570	713	655	625	781				95.5%
TWD1683GE	428	402	502	570	536	670	627	589	737	447	420	525	595	560	700	655	616	770				94%

Stage V*

Engine	CONTINUOUS POWER			PRIME POWER			STANDBY			CONTINUOUS POWER			PRIME POWER			STANDBY			GENERATOR EFF. (%)
	kWm	kWe	kVA	kWm	kWe	kVA	kWm	kWe	kVA	kWm	kWe	kVA	kWm	kWe	kVA	kWm	kWe	kVA	
TAD880GE	97	90	113	129	120	150	142	132	165	113	105	131	151	140	175	166	154	193	93%
TAD881GE	129	120	150	172	160	200	189	176	220	149	138	173	198	184	230	218	203	253	93%
TAD882GE	161	150	188	215	200	250	237	220	276	164	152	191	218	203	254	240	223	279	93%
TAD1380GE	195	182	227	260	242	302	286	266	332	206	191	239	274	254	318	301	280	350	93%
TAD1381GE	227	212	264	303	282	352	333	310	387	237	221	275	316	294	367	347	323	404	93%
TAD1382GE	258	240	300	344	320	400	378	352	440	258	240	300	344	320	400	378	352	440	93%
TWD1683GE	428	402	502	570	536	670	627	589	737	447	420	525	595	560	700	655	616	770	94%

* Indication of emission standard.

Net engine performance acc. to ISO3046, BS5514, DIN6271 and in general SAEJ1349 net power

kWm = kiloWatt mechanical, net with fan

kWe = kiloWatt electrical = kWm x gen. eff.

kVA = kiloVoltAmpere calculations based on a 0.8 power factor = kWe / 0.8